



STABILITY

FITOCLIMA

600 & 1200 STABILITY

TEMPERATURE AND HUMIDITY CHAMBERS
FOR CONTROLLED ENVIRONMENT STORAGE
AND STABILITY TESTING



ICH, GMP, WHO, FDA COMPLIANT





ARALAB is a company specialized in designing, developing, manufacturing and servicing of high quality climatic chambers and controlled environment rooms.

Since 1985 we have been perfecting ways to create and control temperature, humidity, light, air flow and many other environmental conditions.

Only the highest quality components are used to manufacture our chambers so customers can have the best equipment for their research and testing purposes.

Control the Environment. Your Own Climate.



FitoClima Stability Testing chambers provide the environmental control and flexibility to meet the evolving needs of customers throughout the years.

COMMON APPLICATIONS INCLUDE:

- PHARMACEUTICALS
- COSMETICS
- FOOD AND BEVERAGES
- VETERINARY
- STORAGE AND CONSERVATION
- QUALITY CONTROL AND RESEARCH



Certified ISO:9001 for its Quality Management System
Certified ISO:14001 for its Environmental Management System



KEY FEATURES

- Ready to use. No assembly needed
- Minimal footprint, for efficient use of laboratory space
- Future proof design. The interior can be reconfigured at any time for the most efficient use of the available storage space and content dimensions
- Content protection, with configurable high / low temperature and humidity alarms and automatic email notifications
- Remote diagnostics, allowing a fast and accurate technical support
- FDA 21 CFR part 11 compliant software GAMP5
- ECO mode energy saving function
- Compliant and recognized by ICH, FDA, GMP and other leading industry standards




TECHNICAL SPECIFICATIONS

● ● ● ● TECHNICAL DATA FOR FITOCLIMA 600 & 1200 STABILITY CHAMBERS

TEMPERATURE RANGE ^[1]		-5°C to 60°C
TEMPERATURE FLUCTUATION IN TIME		±0.1°C to ±0.2°C
TEMPERATURE UNIFORMITY IN SPACE		± 0,15°C to ± 1,0°C
At 25°C / 60%rH		± 0,24°C
At 30°C / 65%rH		± 0,24°C
At 40°C / 75%rH		± 0,35°C
HUMIDITY RANGE		20% to 95% rH
HUMIDITY FLUCTUATION IN TIME		± 1%rH
HUMIDITY UNIFORMITY IN SPACE		± 2%rH
At 25°C / 60%rH		± 0,83%rH
At 30°C / 65%rH		± 0,69%rH
At 40°C / 75%rH		± 1,20%rH
SHELVES (STANDARD CONFIGURATION) ^[2]		FitoClima 600: 4 stainless steel wire shelves FitoClima 1.200: 4 stainless steel wire shelves
STANDARD SHELF SIZE (mm inches)		FitoClima 600: 645mm x 515mm 25.39 in x 20.28 in FitoClima 1.200: 620mm x 1.320mm 24.4 in x 52 in
STORAGE ^[2]		0.33 m² and 18 Kg weight load (per shelf, evenly distributed) 3.55 ft² and 39.68 lbs (per shelf, evenly distributed)
STORAGE (STANDARD CONFIGURATION) ^[2]		FitoClima 600: 1,33 m² 14.32 ft² FitoClima 1.200: 2,67 m² 28.74 ft²
AIRFLOW		0.2 m/s uniform across the shelves
INTERNAL VOLUMES		FitoClima 600: 543 liters 19.18 cu ft FitoClima 1.200: 1194 liters 42.17 cu ft

● ● ● ● HUMIDITY WORKING RANGE




[1] Temperature and Humidity uniformity performances in Stability Testing chambers according to IEC60068-3-5.

[2] Additional shelves can be fitted (600 model - up to 10 shelves; 1200 model - up to 20 shelves). Reinforced perforated shelves with 40Kg (88 lbs) evenly distributed weight load also available
Performances measured in factory with room temperature between 20°C and 25°C.

DIMENSIONS AND DRAWINGS

FITOCLIMA 600

EXTERNAL DIMENSIONS (HxWxD) (mm) (inches)		1980mm x 745mm x 980mm 77.95 in x 29.33 in x 38.58 in
INTERNAL DIMENSIONS (HxWxD) (mm) (inches)		1330mm x 600mm x 680mm 52.36 in x 23.62 in x 26.77 in




1. Standard refrigeration system is air cooled 2. Services hub installation needs: 3/4" male demineralized water supply valve Conductivity: <50µS/cm , TDS <35PPM Pressure: 1-5 Bar In case of reverse osmosis/cylinder (optional): 3/4" male tap water valve connection Pressure: 1-5 Bar 50mm water drain at floor level	3. Electrical cabinet installation needs: Supply power: 120VAC, 60Hz, 20A / Single Phase + Neutral + Ground Electrical protection: Circuit breaker 20A + N with 30mA differential RJ45 communication port 4. Equipment weight: 170 Kg 375 lbs (approx.) 5. Average heat dissipation: 0,3 kW
--	--

DIMENSIONS AND DRAWINGS

● ● ● ● FITOCLIMA 1.200

EXTERNAL DIMENSIONS (HxWxD) (mm) (inches)		1980 mm×1450 mm×810 mm 77.95 in x 57.09 in x 31.89 in
INTERNAL DIMENSIONS (HxWxD) (mm) (inches)		1330 mm×1320 mm×680 mm 52.36 in x 51.97 in x 26.77 in



- | | |
|---|--|
| 1. Standard refrigeration system is air cooled | 3.  Electrical cabinet installation needs:
Supply power: 120VAC, 60Hz, 24A / Single Phase + Neutral + Ground
Electrical protection: Circuit breaker 32A + N with 300mA differential |
| 2.  Services hub installation needs:
 ¾" male demineralized water supply valve
Conductivity: <50µS/cm, TDS <35PPM
Pressure: 1-5 Bar
In case of reverse osmosis/cylinder (optional):
¾" male tap water valve connection
Pressure: 1-5 Bar
 50mm water drain at floor level | 4.  RJ45 communication port
Average Heat dissipation: 0,5 kW
Equipment weight: 240 Kg 529 lbs (approx.) |

EQUIPMENT DESCRIPTION




CONSTRUCTION & CONTROL

- Multi-color 7-inch touch-screen ClimaPlus© controller
- Open door alarm with configurable time-out function
- Highly resistant stainless-steel
- Polyurethane insulation
- Exterior zinc plated steel and gray epoxy paint
- Pivoting door(s) with spring lock, magnetic gasket and safety lock(s)
- 4 and 5 built-in casters brakes
- 80mm | 3.15" Ø side entry port



ENVIRONMENTAL CONTROL

- Air-cooled, CFC free, mechanical refrigeration by hermetic compressor
- Dual heating technology with hot gas by-pass and stainless steel electric heaters
- Humidification in Stability chambers with clean steam generator
- Humidification in Photostability chamber with ultrasonic generator
- Dehumidification by condensation on the cooling system evaporator
- Models with 'Temperature and Humidity control' are equipped with capacitive sensors; models with 'Temperature control only' are equipped with Resistive NTC sensor
- Air renovation through adjustable lateral port-holes
- Uniform air flow of approximately 0.2m/s across all shelves
- Airflow speed adjustable on the ClimaPlus® controller




RESEARCH PROTECTION AND AUTOMATIC DIAGNOSTICS

- Independent thermostats for maximum and minimum temperature limits
- Automatic cut-off function, in case of excessive heating or cooling
- Configurable maximum and minimum temperature and humidity limits
- Visual and audible alarms for temperature and humidity limits
- Synoptic: a self-diagnostics tool that checks all active components of the system allowing for faster procedures and minimizing any possible downtimes



BUILT-IN DECONTAMINATION

- Heat Decontamination sets temperature to 60°C and other functions are disabled. Duration can be set manually as different contaminations can require custom durations.
- Hydrogen Peroxide bio-decontamination capable: FitoClima 600 / 1200 are resistant to H_2O_2 and now have a bio-decontamination function (only available through Aralab Service Teams) allowing the connection of a H_2O_2 atomizer system developed by Aralab.







ECO MODE

- The ECO Mode button turns on new power saving features
- By decreasing some power related activities (depending on set-point conditions), the energy consumption can decrease, translating in cost savings

CLIMAPLUS HMI CONTROLLER

- Programmable Logic Controller exclusively developed by Aralab for FitoClima chambers
- Easy to use touch-screen interface
- 90mm x 155mm multicolor display (7.2 inches)
- Controls every environmental variable available for any specific FitoClima model (Temperature, Humidity, Lights, Airflow, CO₂, and connected external devices)
- Friendly program editor for creating 32 programs of 24 segments each, allowing the design of complex and comprehensive climatic simulation programs
- Password protection of the controller functions
- Content and research protection feature, with configurable High, Low and Band Temperature and Humidity alarms and automatic notifications
- Managing, monitoring and recording of all alarms
- Non-volatile memory, allowing the automatic restart of previously defined set-points or on-going programs due to power failure, without losing data
- Real-time monitoring of all the functions and active components of the equipment, allowing for a fast and accurate diagnostic in case of malfunction
- Possibility to control and program events by external commands and with external devices
- Graphical view of programs and climatic variables
- Ethernet and Wi-Fi for connecting computers to the controller
- ECO mode energy saving function



FITOLOG SOFTWARE GAMP 5

The FitoLog software pack - FDA 21 CFR part 11 and Eudralex compliant according to GAMP5 risk based approach - is a set of applications designed to facilitate the programming, monitoring, managing and recording of programs and data from the FitoClima chambers. It consists of 3 applications: **FitoLog**, **FitoLogView** and **FitoProgram**.



FITOLOG


Displays and records in real time all data and details related to the set-points, running variables and equipment behaviour. It also retrieves information about the active components of the chamber, running processes, errors, alarms and allows the configuration of periodic or alarm triggered remote notifications (by email or SMS, depending on existing connections and accessories).

User Access Levels can be managed and configured (exclusive for FitoLog FDA 21CFR part11 compliant version)



FITOLOGVIEW

It is a working tool to process data recorded by the FitoLog program. One can view, print and export the log contents to other file types, and analyse the data in other data management software (Excel, Star Office, Access or others).



FITOPROGRAM

This application simplifies the creation of programs and its integration on the chamber ClimaPlus controller. Up to 32 programs, each with 24 segments, can be designed and linked to create detailed environmental profiles and simulations.

FitoProgram not available in the GAMP5 FitoLog version.

CONTENT SECURED WITH ALARMS, NOTIFICATIONS, FAST DIAGNOSTICS AND PROMPT TROUBLESHOOTING

With FitoLog it is possible to gather data from each of the chambers systems, which makes it a very useful tool to diagnose any necessary maintenance. This tool works as the "black box" of the equipment, giving Aralab technicians the necessary data to remotely carry out a fast and efficient diagnostic. All that is needed is a FitoLog file.

COMMON ACCESSORIES

PLEASE CONSULT ARALAB FOR OTHER ITEMS

FitoLog® software pack for PC/Laptops, enabling data monitoring, logging and managing operations directly on a computer – FDA 21 CFR part 11 and Eudralex compliant according to GAMP5

IQ, OQ, PQ procedures and documentation

ISO 17025 Temperature and Humidity calibrations

Additional stainless steel wire shelves

Additional lateral entry port

Reinforced stainless steel shelves for heavier test specimens

20 liter water tank with electric pump and security valve

Conductivity meter, for water quality control

Wireless connections

Double glazed glass doors

Additional Drying Capacity



FitoLog FDA 21 CFR part 11 compliant



External Water tank



Reinforced SS shelves (40Kg load).

Features and specifications are subject to change. Aralab continuously studies ways to further develop its products to achieve better performances and overall product quality. As a result, characteristics and specifications provided in this document may be subject to changes.

Let's meet!

aralab@aralab.pt

www.aralab.pt

T: +351 219 154 960



Configure your
FitoClima chamber

See it on the
Showroom

[f/AralabChambers](https://www.facebook.com/AralabChambers)

[in/company/aralab](https://www.linkedin.com/company/aralab)

[y/user/AralabChambers](https://www.youtube.com/user/AralabChambers)

[x/Aralab_](https://www.x.com/Aralab_)

[@aralabchambers](https://www.instagram.com/aralabchambers)



Control the environment

Your own climate